

## Networked Smart Plugs

Optimizing the consumption of self-produced power

External appliances can be turned on and controlled by the Solar-Log 300, 1200 and 2000 via smart plugs. To optimize the consumption of self-produced power automatically, a total power consumption meter is required as well as a networked smart plug. A maximum of 10 networked smart plugs can be controlled.



Technical data	AllNet Standard 1.8 kW	AllNet WLAN 3.5 kW	Belkin WeMo Insight Switch
Maximum load	1600 - 2000 watts	1600 - 3500 watts	3680 watts
Maximum current	8 A	16 A	16 A
Control	TCP / IP	TCP / IP	WLAN 2.4 Ghz
Status	On / Off	On / Off	On / Off
Connector	C (Europlug), F (Schuko plug)	C (Europlug), F (Schuko plug)	B (Nema 5-15, 2 pole), C (Europlug), F (CEE 7/4 Schuko plug), I (AS/NZS 3112)
Dimensions (w x h x d) in mm, weight	68 x 40 x 128, 200 g	68 x 60 x 128, 200 g	130 x 160 x 100, 998 g
Warranty	2 years	2 years	2 years

### Article number

AllNet Networked Smart Plugs standard 1.8 kW	255429
AllNet Networked Smart Plugs WLAN 335 kW	255616
Belkin WeMo Insight Switch	255841